



Series	Connector Type	Contact Plating	Material	Pin Length mm	Number of Contacts
<b>F201</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>DXXX</b>	<b>XX</b>
(Female Header Dual Row) F201 (2.54 H:8.5)	S: Straight Type	G: Gold Flash T: Tin Plated A: 10U"Gold B: 15U"Gold C: 20U"Gold ©Duplex Plating D: Gold Flash/Tin (Standard:G)	P: PBT N: Nylon-6T L: Nylon-66 (Standard:P)	S-D D030 (Standard:S-D030)	(04 TO 80 Contacts)

△ 此符號表示重點管控尺寸

DESCRIPTION(內容): <b>2.54mm Female Header H:8.5 W:5.0 180°</b>  PART NO: (料號) <b>F201-SG_-D030-XX</b> DWG NO(圖號):	DRAWN(製圖): CHECKED(確認):	GENERAL TOLERANCE: (公差) X. ±0.30 X.° 35.0° .X 30.20 .X° 33.0° .XX 30.15 .XX° 30.0°	REV: <b>A/1</b> UNIT: <b>mm</b> SIZE: <b>A4</b> SHEET: <b>1/1</b>	REV <b>1</b> <b>1</b> <b>2</b> <b>3</b>	DESCRIPTION    	DATE    
	APPROVAL(核准):	SCALE(比例): <b>1:XX</b>				