



Recommended P.C.Board Hole Layout

所有材料為
"環保材料"
2006.11.03
RoHS

Specifications

Current Rating :3 Amps
 Insulator Resistance :5000 Megohms Min.
 Contact Resistance :20 m ohms max.
 Dielectric Withstanding :AC 1000 V
 Operating Temperature :-40°C ~ +105°C
 Max Processing Temp :260°C for 3~5 sec Max.
 Contact Material :Phosphor Bronze
 Insulator Material :Polyester, UL 94V-0
 Standard :Nylon-6T
 Finish: Tin, Gold or Duplex Plated
 Standard: Gold Flash all over
 Note:
 Duplex plating: Gold Plated on contact area,
 Tin on solder area

Series	Connector Type	Contact Plating	Material	Pin Length mm	Number of Contacts
F208	- X	X	X -	DXXX	-XX
(Female Header Dual Row) F208(2.54 H:8.1 W:5.9)	M:SMT TYPE	G:Gold Flash T:Tin Plated A:10U"Gold B:15U"Gold C:20U"Gold ©Duplex Plating	N:Nylon-6T (Standard:N)	M-D D112	(04 TO 80 Contacts)
		D:Gold Flash/Tin (Standard:G)			

△ 此符號表示重點管控尺寸

DESCRIPTION(內容)	DRAWN(製圖)	GENERAL TOLERANCE:(公差)	REV: R0	REV	DESCRIPTION	DATE
2.54mm Female Header H:8.1 W:5.9 SMT Nylon-6T	彭維明	.X .XXX .XX .X° .XXX .XX°	UNIT: mm	R0		2006.03.06
PART NO: (料號) F208-MGN-D112-XX	CHECKED(確認):	SCALE(比例): 1:XX	SIZE: A4	R1		
DWG NO(圖號):	APPROVAL(核准):		SHEET: 1/1	R2		
				R3		