



Specifications

Current Rating	: 1 Amp
Insulator Resistance	: 1000 Megohms Min.
Contact Resistance	: 20 m ohms max.
Dielectric Withstanding	: AC 500 V
Operating Temperature	: -40°C ~ +105°C
Soldering Temperature	: 260°C for 3~5sec Max.
Contact Material	: Phosphor Bronze
Insulator Material	: Polyester, UL 94V-0
Standard	: Nylon-6T
Finish	: Gold Plated
Standard	: Gold Flash all over

Series	Connector Type	Contact Plating	Material	Pin Length mm	Number of Contacts	Other
<u>F504</u>	- <u>X</u>	<u>X</u>	<u>X</u>	- <u>DXXX</u>	- <u>XX</u>	- <u>XT</u>
(Female Header Single Row) F504 (1.27 H:3.4)	M: SMT Type	G: Gold Flash T: Tin Plated A: 10U"Gold B: 15U"Gold C: 20U"Gold ©Duplex Plating	N: Nylon-6T (Standard: N)	M-D D034	(02 TO 40 Contacts)	AT: TYPE A BT: TYPE B

所有材料為
環保材料
2008.3.18
RoHS

△ 此符號表示重點控管尺寸

DESCRIPTION(內容): 1.27mm Female Header H:3.4 W:2.2 SMT Nylon-6T	DRAWN(製圖): Larry	GENERAL TOLERANCE: (公差)	REV: R3	REV	DESCRIPTION	DATE	
	CHECKED(確認): MANDY	.X .XXXX .XX .X° .XXX .XX°	UNIT: mm	R0	舊料號: CPC340605	2005.08.13	
	PART NO: (料號) F504-MGN-D034-XX-XT	APPROVAL(核准): JOHNNY	SCALE(比例): 1:XX	SIZE: A4	R1	舊料號: F504-MGN-D034-XT , 更新料號	2005.12.04
	DWG NO(圖號):			SHEET: 1/1	R2	端子規格由 04D 改為 04B	2007.08.13
				R3	新增 LAO 圖 PIN 寬度 & 修正寬度標示範圍	2014.01.24	