



Specifications

Current Rating	: 0.8 Amp
Insulator Resistance	: 900 Megohms Min.
Contact Resistance	: 20 m ohms max.
Dielectric Withstanding	: AC 500 V
Operating Temperature	: -40°C ~ +105°C
Soldering Temperature	: 260°C for 3~5sec Max.
Contact Material	: Phosphor Bronze
Insulator Material	: High Temperature Thermoplastic. UL 94V-0
Standard	: LCP
Finish	: Gold Plated
Standard	: Gold Flash all over

Series	Connector Type	Contact Plating	Material	Pin Length mm	Number of Contacts	Other
F703	X	X	X	DXXX	-XX	-XT
(Female Header Dual Row) F703(1.00 H:2.00 W:1.5)	M:SMT Type	G:Gold Flash T:Tin Plated A:10U"Gold B:15U"Gold C:20U"Gold ©Duplex Plating D:Gold Flash/Tin (Standard:G)	C:LCP (Standard:C)	S-D D029	(06 TO 10 Contacts)	AT:A TYPE BT:B TYPE

所有材料為
"環保材料"
2014.12.22
RoHS

DESCRIPTION(內容):	DRAWN(製圖):	GENERAL TOLERANCE:	REV:	REV	DESCRIPTION	DATE
1.0mm Female Header SMT H:2.0 W:1.5 LCP	黃炳秋	(公差)	A/1	1	△此符號表示重點管控尺寸	2014.12.11
PART NO: (料號) F703-MGC-D029-XX-XT	CHECKED(確認): 黃炳秋	X. ±0.30 X.° ±5.0° .X ±0.20 .X° ±3.0° .XX ±0.15 .XX° ±1.0°	UNIT: mm	2		
DWG NO(圖號):	APPROVAL(核准): 鄧文廣	SCALE(比例): XX:XX	SIZE: A4	3		
			SHEET: X/X	4		