



SPECIFICATIONS

Current rating : 0.5A AC, DC
 Voltage rating : 30V AC, DC
 Temperature range : -25°C ~ +85°C
 Contact resistance : 20mΩMax
 Insulation resistance : 100MΩMin
 Withstanding voltage : 200 VAC/minute
 Finished : Matte Tin-plated
 Housing Material : Nylon-6T, UL94 V-0

P.C.B LAYOUT

Circuits	Dimension mm		Circuits	Dimension mm	
	A	B		A	B
2PIN	0.80	3.80	12PIN	8.80	11.80
3PIN	1.60	4.60	13PIN	9.60	12.60
4PIN	2.40	5.40	14PIN	10.40	13.40
5PIN	3.20	6.20	15PIN	11.20	14.20
6PIN	4.00	7.00	16PIN	12.00	15.00
7PIN	4.80	7.80	17PIN	12.80	15.80
8PIN	5.60	8.60	18PIN	13.60	16.60
9PIN	6.40	9.40	19PIN	14.40	17.40
10PIN	7.20	10.20	20PIN	15.20	18.20
11PIN	8.00	11.00	21PIN	16.00	19.00
			22PIN	16.80	19.80

DESCRIPTION : 0.8MM WAFER 90° SMT TYPE (環保材料)	DRAWN : 鄧文廣	GENERAL TOLERANCE :	REV: A/3	REV	DESCRIPTION	DATE	
	CHECKED :	.X ±0.08 .XX ±0.05 .XXX ±0.03	UNIT: mm	1	△此符號表示重點管控尺寸	2007.09.12	
	PART NO: CC0801-W08R-XX	APPROVAL :	SCALE: 1:1	SIZE: A4	2	修改料號: C0801-W08R-XX	2008.07.22
				SHEET: 1/1	3	更正Layout圖	2009.07.16
				4			