



Specifications:

- Material: Nylon 66, UL 94V-0
- Voltage Rating: 250V
- Current Rating: 5A
- Withstand Voltage: 1500V AC/Minute
- Insulation Resistance: 1000MΩ min.
- Temperature Range: -25°C~+85°C
- Contact Resistance: Initial value/10mΩ max.
After environmental testing/20mΩ max.
- Standard Color: Black

Dimensional & Ordering Information:

Circuits	Part No	Dimensions mm	
		A	B
02	CMF-H300M-1×02	3.00	7.0
03	CMF-H300M-1×03	6.00	10.0
04	CMF-H300M-1×04	9.00	13.0
05	CMF-H300M-1×05	12.00	16.0
06	CMF-H300M-1×06	15.00	19.0
07	CMF-H300M-1×07	18.00	22.0
08	CMF-H300M-1×08	21.00	25.2
09	CMF-H300M-1×09	24.00	28.2
10	CMF-H300M-1×10	27.00	31.2
11	CMF-H300M-1×11	30.00	34.2
12	CMF-H300M-1×12	33.00	37.2

所有材料為
"環保材料"
2009.5.05
RoHS

DESCRIPTION(內容): 3.0mm (.118") Micro-Fit connector PART NO: (料號) CMF-H300M-1×XX DWG NO(圖號): 5750-H-1X	DRAWN(製圖): GONG	GENERAL TOLERANCE: (公差) .000 : ±0.08 .00 : ±0.13 .0 : ±0.25	REV: R1 UNIT: mm SIZE: A4 SHEET: 1/1	REV R0 R1 R2 R3	DESCRIPTION RELEASE 2014年8月料號P數編碼統一兩碼	DATE 2009.05.05 2015.01.21	
	CHECKED(確認): MANDY						APPROVAL(核准): JOHNNY