



SPECIFICATIONS

Electrical

Current Rating: 1A AC, DC
 Voltage Rating: 125V AC/ max.
 Operating Temp.: -20°C ~ +85°C
 Insulation Resistance: 100MΩ/ min.
 Dielectric Withstanding Voltage: 250V AC/ min.
 Contact Resistance: 20mΩ/ max.

Material

Material: Nylon66, UL94V-0

Poles	Dimension mm (in.)		Part No.	Note.
	A	B		
2	1.25(0.049)	4.25(0.167)	CX-H125-02	
3	2.50(0.098)	5.50(0.217)	CX-H125-03	
4	3.75(0.148)	6.75(0.266)	CX-H125-04	
5	5.00(0.197)	8.00(0.315)	CX-H125-05	
6	6.25(0.246)	9.25(0.364)	CX-H125-06	
7	7.50(0.295)	10.50(0.413)	CX-H125-07	
8	8.75(0.344)	11.75(0.463)	CX-H125-08	
9	10.00(0.394)	13.00(0.512)	CX-H125-09	
10	11.25(0.443)	14.25(0.561)	CX-H125-10	
11	12.50(0.492)	15.50(0.610)	CX-H125-11	
12	13.75(0.541)	16.75(0.659)	CX-H125-12	
13	15.00(0.591)	18.00(0.709)	CX-H125-13	
14	16.25(0.640)	19.25(0.758)	CX-H125-14	
15	17.50(0.689)	20.50(0.807)	CX-H125-15	

所有材料為
 "環保材料"
 2006.08.09
 RoHS

PART NO: (料號)	DESCRIPTION(內容): 1.25mm Wire-to-Board Housing	DRAWN(製圖): mandy	GENERAL TOLERANCE: (公差) X.XX ± 0.15 X.X ± 0.25	REV:	REV	DESCRIPTION	DATE
				R2			
CX-H125-XX		CHECKED(確認): MANDY		UNIT:	R0	環保料	2006.08.09
				mm	R1	修改絕緣阻抗單位	2007.04.04
				SIZE:	R2	2014年料號編碼P數統一兩碼	2014.10.17
				A4	R3		
DWG NO(圖號): 1250-XX		APPROVAL(核准): JOHNNY	SCALE(比例): FREE				