

TOF-3465BMR-B5.7-S3.5


Four Digit Display LED

Part Number	Chip		Face Color	Segment Color
	Material	Source Color		
TOF-3465BMR-B5.7-S3.5	AlGaInP	Ultra-red	Black	White

Features

- (0.36") 9.00mm digit height
- Common anode
- I.C. compatible
- Low power requirement
- RoHS compliant

Package Dimensions & Internal Circuit Diagram



Notes: 1、 All dimensions are in millimeters, tolerance: ± 0.25 ; Angle: $\pm 3^\circ$

2、 The acceptable bending is less than 0.15.

3、 The maximum displacement of REF and spacer 0.25mm

Absolute Maximum Rating @ Ta=25°C

Parameter	Maximum Rating	Unit
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	80	mA
Power Dissipation	60	mW
Continuous Forward Current	20	mA
Reverse Voltage	5	V
Operating Temperature Range	-25°C to +85°C	
Storage Temperature Range	-30°C to +85°C	
Lead-Free Solder Temperature(1/16 Inch Below Seating Plane)	260°C for 3 Sec	

Electrical / Optical Characteristic @ Ta=25°C

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition	Grade
Luminous Intensity segment	I _v	10384	15524		ucd	I _F =10mA	
Dominant Wavelength	λ _d		630		nm	I _F =20mA	
Spectral Line Half-Width	Δλ		15		nm	I _F =20mA	
Forward Voltage	V _F	1.8	2.0	2.3	V	I _F =20mA	
Reverse Current	I _R			100	μA	V _R =5V	
Luminous Intensity Matching Ratio	I _v -m			2.0:1		I _F =20mA	